

CAT 20:1 C-20 Air Assisted Airless Unit



C.A. Technologies' C-20 AAA is designed with a 20 to 1 fluid ratio for higher viscosity materials and multi-gun operation. This unit incorporates a totally enclosed throat seal to reduce contamination. The fluid section and air motor are built for easy "field" repairs with fewer parts lowering maintenance costs and equipment down time. The magnetic no stall trip mechanism insures smooth pump stroke transition with virtually no "surge" or "wink" in spray pattern. The standard fluid section utilizes a spring seal configuration on the lower and self-adjusting "V" packing on the upper. An optional self-adjusting "V" packing for the lower is available for abrasive coatings.

Features

- Durable and dependable pump for continuous operation
- 100 psi maximum inlet pressure
- 2000 psi maximum fluid pressure
- 2 GPM displacement for automatic multiple gun applications (8 guns up to 13 thousandths tip)
- Optional fluid section fluid filter with multiple outlets
- Available in a cart mount or wall mount with 5 or 55 gallon siphon assemblies
- Throat seal is completely enclosed to reduce contamination with a sight gauge for ease of checking lubricant levels
- New "CAT fast clamp" provides an easy and rapid removal of the fluid section from the air motor for any maintenance needs
- Pumps come standard with an all stainless steel fluid section and can be used for most solvent and waterborne coatings, paints, pigmented lacquers, pre and post catalyzed materials and primers
- C-20pumps are available for single or multiple gun outfits and use with the Bobcat, Cougar, or Bobcat Automatic guns









CAT 20:1 C-20 Air Assisted Airless Unit

C-20 Online Configurator

	Upper Seal	Lower Seal	Fluid Inlet	Fluid Outlet	Mounting/Siphon Assy	QTY of Guns	Gun+Tip	QTY of Hose	Hose 3/16"
	S=Self Adjusting	🗾 U=U Cup	0=3/4" NPT (F)	0=1/2"NPT (F)	C0=Cart, No Siphon	0	🔲 0=No Gun	0	🗌 0=No Hose
	🔲 M=Manual Take-Up	P=V-Packing	4=1/2" SAE (M)	2=1/4"NPS (M)	🔲 C5=Cart, 5 gal Siphon	— 1	B=Bobcat	— 1	A=25' Hose
			6=3/4" SAE (M)	🗾 F=Filter Assy	📄 C55=Cart, 55 gal Siphon	2	C=Cougar	<u> </u>	🔲 B=35' Hose
0.00				🗾 FSS=Stainless Steel	🔲 W0=Wall, No Siphon	– 3	AB=Auto Bobcat	<u> </u>	C=50' Hose
C-20				Filter Assy	🔲 W5=Wall, 5 gal Siphon	– 4		– 4	
					🔲 W55=Wall, 55 gal Siphon	5		5	
						6		6	
						7		7	
						8		8	

*The top row of each column will be used as the standard default if an option in that column is not selected. For multiple guns and hose packages, please add requested quantities after the gun letter, and hose numbers. I.E. C20-MU42-C5-2B411-2A (20:1 pump with manual take-up upper seal, U Cup lower seal, 1/2" inlet, 1/4" outlet, cart mounted 5 gallon siphon, (2)Bobcat guns and (2) 25' hose assemblies)** Price calculators are available at www.spraycat.com



Hose Sets

Description	Part Number		
25' - 3/16" AAA Hose Set	53-402A		
25' 1/8" AAA Hose Set	53-404A		



Siphon Hose Assemblies

-	
Description	Part Number
1/2" - 5 Gallon	74-520
1/2" - 55 Gallon	74-524
3/4" - 5 Gallon	74-530
3/4" - 55 Gallon	74-531



Siphon Hose Filters

Description	Part Number		
1/2" - Filter Assembly (Economy)	74-562		
1/2" - Filter Assembly (Premium)	74-511		



Manual Spray Guns

Description	Part Number		
Cougar Spray Gun (Full Size)	BXXX		
Bobcat Spray Gun (Compact)	CXXX		
GM 4700AC (Full Size)	GM4700-BLXXX		

C.A.Technologies - Brand of the Wagner Group

 Liquid Division
 Powde

 337 South Arthur Ave
 1770 F

 Louisville, C0 80027
 Plymou

 T 888.820.4498
 T 800.4

 F 303.438.5708
 F 630.4

 www.spraycat.com
 www.

Powder Division 1770 Fernbrook Lane Plymouth, MN 55447 T 800.473.2524 F 630.503.2377 www.wagnersystemsinc.com







Automatic Spray Guns

Description	Part Number		
Automatic Bobcat	ABXXX		



Fluid Filters

Description	Part Number		
Fluid Filter (Standard)	52-410		
Fluid Filter (Stainless Steel)	52-420		

