

Jaguar 100H

100 Series HVLP General Purpose

The Jaguar 100H is a high quality general purpose gravity feed sprayer. Designed with an all stainless steel fluid passage, this spray gun can be set up with low volume air caps for small HP compressor use which makes it perfect for on site jobs.

Jaguar 100H

Features

- Forged Aluminum Body
- Stainless Steel Fluid Passages
- Great for Onsite or Production applications
- HVLP - 65% Transfer Efficient or Better
- Available with the Low CFM 21-1090 Air Cap for Portability with On Site Jobs



Jaguar 100H

"HVLP Versatility"

Gravity Cups



700 mL
(Plastic)
51-400



700 mL
(Aluminum)
51-401



1000 mL
(Aluminum)
51-403

CAT Packs



CP-J100H



CP-J100H-PPS



Nozzle Chart for Jaguar 100H

Material Type	Fluid Orifice x Air Cap	Maximum Pattern Width	Pressure / Siphon
Very Thin less than 16 sec. Zahn #2 inks, dyes, solvents, stains	0.5, 0.8 mm x 1090	10	P
	0.5, 0.8 mm x 1092	11	P
Thin 16 to 20 sec. Zahn #2 lacqers, enamels, primers, sealers	1.0, 1.2 mm x 1092	11	P
	1.0, 1.2 mm x 1093	12	P
Medium 21 to 30 sec. Zahn #2 automotive base coat enamels, primers, epoxies, urethanes, automotive clear coat	1.3, 1.4, 1.5 mm x 1093	12	P
	1.3, 1.4, 1.5 mm x 1095	12	P
	1.3, 1.4, 1.5 mm x 1097	13	P
Heavy over 30 sec. Zahn #2 heavy body primers, high solid enamels, high solid automotive coatings, adhesives	1.6, 1.7 mm x 1095	12	P
	1.6, 1.7 mm x 1097	13	P
	1.6, 1.7 mm x 1195	13	P
	1.6, 1.7 mm x 1197	14	P

Air Caps for Jaguar100H

Air Caps	Retaining Rings	Max Inlet Pressure	CFM @ Max Inlet Pressure
21-1090	21-1001	15 PSI	6 CFM @ 15 PSI
21-1091		15 PSI	8 CFM @ 15 PSI
21-1092		15 PSI	8 CFM @ 15 PSI
21-1093		18 PSI	10 CFM @ 18 PSI
21-1094		33 PSI	13 CFM @ 33 PSI
21-1095		50 PSI	20 CFM @ 50 PSI
21-1097		50 PSI	20 CFM @ 50 PSI
21-1195	Included	50 PSI	20 CFM @ 50 PSI
21-1197		50 PSI	20 CFM @ 50 PSI