

Pressure Tanks

Standard Pressure Tanks (2.5 Gallon - 15 Gallon)



51-202



51-204





51-504





51-702

			2.5 Ga
Tanks	Part #	Regulators	Agitator
	51-200	0	None
	51-201	1	None
	51-202	2	None
Standard	51-203	1	Air
Stariuaru	51-204	2	Air
	51-205	0	Air
	51-207	2	None
	51-209	2	Air
	51-210	0	None
	51-211	1	None
Bottom Outlet	51-212	2	None
	51-213	1	Air
	51-214	2	Air
	51-215	0	Air

Tank Inside Dimensions: Diameter = 10 1/2" Depth = 8 3/4'

tanks have a 3/4" fluid outlet w/ ball valve. Gasket: 51-220

llon Pressure Tanks

Description

The 2.5 gallon non-ASME tank from C.A.T. is constructed of heavy gage steel. The tank has wheels for maneuverability or optional stationary feet. All 2.5 gallon tanks come with a ridged

The bottom outlet 2.5 gallon non-ASME tank from C.A.T. is constructed of heavy gage steel. The tanks have a baked on

coating and come with or without agitation. The tank has wheels for maneuverability or optional stationary feet. All bottom outlet

> <u>Tank Liners:</u> 51-261-12 (12 Pack - Rigid) 51-231-10 (10 Pack - Bag)

	5 Gallon Pressure Tanks					
Tanks	Part #	Regulators	Agitator	Description		
	51-500	0	Hand			
	51-501	1	Hand	The 5 gallon non-ASME tank from C.A.T. is constructed of heavy		
	51-502	2	Hand	,		
	51-503	1	Air	gage steel. This tank comes standard with dual fluid outlets and		
Standard	51-504	2	Air	ball valves. The tank has wheels for maneuverability or optional		
	51-505	0	Air	stationary feet. Maximum working pressure is 80 PSI. The tank		
	51-506	0	None	comes with a 2" dia. fill port.		
	51-507	1	None			
	51-508	2	None			
	51-510	0	None	The bottom outlet 5 gallon non-ASME tank from C.A.T. is		
	51-511	1	None	constructed of heavy gage steel. The tanks have a baked on		
Bottom	51-512	2	None	coating and come with or without agitation. The tank has wheels		
Outlet	51-513	0	Air	, ,		
- 2	51-514	1	Air	for maneuverability or optional stationary feet. All bottom outlet		
	51-515	2	Air	tanks have a 3/4" fluid outlet w/ ball valve.		
Tonk Incido	Dimonoion	o: Diamotor =	10 1/"	Cooket: 51 520 Took Linere: 51 542 10 (10 Dook)		

<u>Tank Inside Dimensions:</u> Diameter = 12 ½ Depth = 15 1/2"

Gasket: 51-520

Tank Liners: 51-543-10 (10 Pack)

	10 Gallon Pressure Tanks				
Tanks	Part #	Regulators	Agitator	Description	
Standard	51-550 51-551 51-552 51-553 51-554 51-555 51-556 51-557 51-558	0 1 2 1 2 0 0 0	None None None Air Air Air Hand Hand	The 10 gallon non-ASME tank from C.A.T. is constructed of heavy gage steel. This tank comes standard with dual fluid outlets and ball valves. The tank has wheels for maneuverability or optional stationary feet. Maximum working pressure is 80 PSI. The tank comes with a fill port.	
Bottom Outlet	51-560 51-561 51-562 51-563 51-564 51-565	0 1 2 0 1 2	None None None Air Air	The bottom outlet 10 gallon non-ASME tank from C.A.T. is constructed of heavy gage steel. The tanks have a baked on coating and come with or without agitation. The tank has wheels for maneuverability or optional stationary feet. All bottom outlet tanks have a 3/4" fluid outlet w/ ball valve.	
Tank Inside	Tank Inside Dimensions: Diameter = 12 ½"		: 12 ½"	<u>Gasket:</u> 51-520 <u>Tank Liners:</u> 51-543-10 (10 Pack)	

15 Gallon Pressure Tanks				
Tanks	Part #	Regulators	Agitator	Description
Standard	51-701 51-702	1 2		The 15 gallon non-ASME tank from C.A.T. is constructed of
Standard	51-703	1		heavy gage steel. This tank comes standard with dual fluid outlets and hall valves. Maximum working pressure is 80 PSI

Tank Inside Dimensions: Diameter = 14 1/2" Depth = 21 1/2"

Gasket: 51-720

Coating Atomization Technologies: 337 S. Arthur Ave. Louisville, CO 80027

Depth = 21 1/2"

Phone: 888.820.4498, Fax: 303.438.5708 www.spraycat.com



SS Pressure Tanks

Stainless Steel Pressure Tanks (2.5 Gallon - 12.5 Gallon)



51-802



51-804



51-914



51-854



51-852



C.A. Technologies Stainless Steel Tanks are the ideal solution for virtually all waterborne and corrosive coatings.

○ C.A.T. SS tanks are fabricated from heavy weight 304 stainless steel: tank lid, shell, pickup tube, fluid outlets and all wetted parts are stainless steel.

	2.5 Gallon Stainless Steel Pressure Tanks					
Tanks	Part #	Regulators	Agitator	Description		
	51-800	0	None			
	51-801	1	None	The 2.5 gallon stainless steel tank from C.A.T. is constructed of		
Stainless	51-802	2	None	all S.S. inside and out. The tank has wheels for maneuverability		
Steel	51-803	1	Air	1		
	51-804	2	Air	or optional stationary feet.		
	51-805	0	Air			
Ctairless	51-910	0	None	The bottom outlet 2.5 gallon non-ASME tank from C.A.T. is		
Steel <u>51-912</u> <u>2</u> Nor	51-911	1	None	constructed of stainless steel and are available with or without		
	51-912	2	None	agitation. The tanks have wheels for maneuverability or optional		
	Air	, ,				
Outlet	51-914	2	Air	stationary feet. All bottom outlet tanks have a 3/4" fluid outlet w/		
Outlet	51-915	0	Air	ball valve.		

Tank Inside Dimensions: Diameter = 10 1/2" Depth = 8 3/4"

Gasket: 51-220

Tank Liners: 51-261-12 (12 Pack - Rigid) 51-231-10 (10 Pack - Bag)

	5 Gallon Stainless Steel Pressure Tanks					
Tanks	Part #	Regulators	Agitator	Description		
	51-850	0	None			
	51-851	1	None	The 5 gallon stainless steel tank from C.A.T. is constructed of all		
Stainless	51-852	2	None	S.S. inside and out. The tank has wheels for maneuverability or		
51	51-853	1	Air	,		
	51-854	2	Air	optional stationary feet.		
	51-855	0	Air			
Ctairless	51-920	0	None	The bottom outlet 5 gallon non-ASME tank from C.A.T. is		
Stainless 51-921 51-922	51-921	1	None	constructed of stainless steel and are available with or without		
	2	None				
Bottom	51-923	1	Air	agitation. The tanks have wheels for maneuverability or optional		
Outlet	51-924	2	Air	stationary feet. All bottom outlet tanks have a 3/4" fluid outlet w/		
Outlet	51-925	0	Air	ball valve.		

<u>Tank Inside Dimensions:</u> Diameter = 12 ½" Depth = 15 1/2"

Gasket: 51-520

Tank Liners: 51-543-10 (10 Pack)

	12.5 Gallon Stainless Steel Pressure Tanks					
Tanks	Part #	Regulators	Agitator	Description		
Stainless Steel	51-880 51-881 51-882 51-883 51-884 51-885	0 1 2 1 2 0	None None None Air Air	The 12.5 gallon stainless steel tank from C.A.T. is constructed of all S.S. inside and out. The tank has wheels for maneuverability or optional stationary feet.		
Stainless Steel Bottom Outlet	51-940 51-941 51-942 51-943 51-944 51-945	0 1 2 1 2 0	None None None Air Air	The bottom outlet 12.5 gallon non-ASME tank from C.A.T. is constructed of stainless steel and are available with or without agitation. The tanks have wheels for maneuverability or optional stationary feet. All bottom outlet tanks have a 3/4" fluid outlet w/ball valve.		

<u>Tank Inside Dimensions:</u> Diameter = 14 ½" Depth = 19"

Gasket: 51-890

Coating Atomization Technologies: 337 S. Arthur Ave. Louisville, CO 80027

Phone: 888.820.4498, Fax: 303.438.5708 www.spraycat.com